

GATEWAY COMM. CARPET



PRODUCT SPECIFICATIONS

Physical Construction

Style	Gateway Commercial Carpet
Fiber Type	100% ColorStrand Solution Dyed Nylon
Construction	Textured Level Loop
Pile Weight	26oz
Dye Method	Solution Dyed
Gauge	1/10th L
Stitches Per Inch	8.67
Pile Thickness/Height	0.150
Yarn Twists Per Inch	n/a
Density	5176
Total Weight	54.41
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
Width	12'
Pattern Repeat	None
Performance	Heavy Commercial

Environmental

CRI Indoor Air Quality Green Label Plus (8216)

Testing

FHA Information (MEA# 45573)	Type I & II: Class 1
Performance Appearance Retention (PAR) Rating	4.50
Static (AATCC-134)	3.2 K.V. (step) 3.5 K.V. (scuff)
Critical Radiant Flux Panel (ASTM E-648)	Class I
Smoke Density (ASTM E-662)	116 (flame only)
Pill Test - 16CFR-1630.4 (FF-1-70)	Pass

Warranties

10 Year Limited Wear Warranty	10 Year Limited Stain Resistance Warranty
10 Year Limited Colorfastness to Light Warranty	Permanent Anti-Static Control

Installation

Follow CRI Carpet Installation Standards	
Stretch-In or Glue-Down	
Recommended Adhesive	TA-9680
Recommended Seam Cement	WF Taylor 775 or WF Taylor 2075
Recommended Cleaner	FreshFloors by WF Taylor