

MEDLEY XL

PRODUCT SPECIFICATIONS

TYPE	
Construction	Engineered Vinyl Click (EVC) Waterproof Premium Polymer Core
Classification	Multilayered Flooring
Wear Layer	Ceramic Bead Textured Finish w/ 4-Sided Micro-Beveled Edges
Size	7" wide x 48" length
Overall Thickness	8mm thick
Wear Layer Thickness	30mil
Pieces Per Carton	8
Cartons Per Pallet	70
Coverage Per Carton	18.66 sq. ft.
Weight Per Carton	30 lbs

TEST	
Resistance to Impact (ASTM F1265-03a)	No Cracking
Abrasion Resistance (ASTM D4060-2010)	41,000 cycles/failure
Castor Chair Resistance (NALFA 3.9)	Class 3, Commercial
Static Load Limit (ASTM F970-07)	0.004", Passes @ 250 psi
Static Coefficient of Friction (ASTM 1028-07)	Pass 0.68 ADA/OSHA requirement
Dimensional Stability (ASTM 2199-09)	Pass \leq 0.51mm/305mm
Density (ASTM D6111-13a)	> 0.8g/cc
Resistance to Heat (ASTM F1514-03)	Meets < 8.0 Delta E Requirement
Resistance to Light (ASTM F1515-003)	Meets < 8.0 Delta E Requirement
Thickness Swell (ASTM D7519-11)	Class 4, Heavy Commercial
Critical Radiant Flux (ASTM E648-08)	Class 1
Resistance to Chemicals (ASTM F925-13)	Pass
FloorScore Indoor Air Quality	Certified

INSTALLATION | CLICK

Angle & Tap Lock + 1mm Attached Pad

WARRANTIES

Lifetime Residential / 15 Year Commercial / 15 Year Multi-Family

