

# EXPEDITION

## PRODUCT SPECIFICATIONS



### Product Specifications

#### Type

Construction	2mm Glue Down Luxury Vinyl Plank
Classification	ASTMF 1700, Class III, type B Solid Vinyl Floor Tile/Plank
Wear Layer	Enhanced Polyurethane Finish
Wear Layer Thickness	12 mil
Size	6" wide x 48" length
Overall Thickness	2.0 mm
Square Feet Per Carton	35.96
Cartons Per Pallet	78
Weight Per Carton	28 lbs

#### Installation

Installation Adhesive: Residential & Multi-Family - WF Taylor Dynamic  
 Installation Adhesive: Commercial - WF Taylor Pinnacle

#### Warranties

20 Year Residential and Multi-Family, 5 Year Light Commercial

#### Test Method & Requirements

Solid Vinyl Floor Tile	ASTMF1700	Class III, Type B
Flexibility	ASTM F137	Meets
Thickness	ASTM F386	Meets
Wear Layer Thickness	ASTM F410	Meets
Stain/Chemical Resistance	ASTM F925	Meets
Resistance to Heat	ASTM F1514	Meets
Resistance to Light	ASTM F1515	Meets
Residual Indentation	ASTM F1914	Meets
Size & Squareness	ASTM 2055	Meets
Dimensional Stability	ASTM F2199	Meets
Static Coefficient Polished Surface	ASTM D2047	Exceeds Industry Standard
Flammability/Radiant Flux	ASTM E648	Class I
Static Load	ASTM F970	>250 lbs
Static load limit	ASTM F970, 0.005 in or les	2,000 psi
Smoke Density	ATSM E-662	Meets