

LAMINATE 12 MM + 2 MM EVA ATTACHED PAD



Topeka | SCLA0201



Augusta | SCLA0202



Lansing | SCLA0203



Lincoln | SCLA0204



Albany | SCLA0205



Harrisburg | SCLA0206



Richmond | SCLA0207



Jackson | SCLA0208

SPECIFICATIONS

Construction	12 mm Water Resistant Core + 2 mm EVA Attached Pad
Dimensions	9.5" Wide x 60" Long, 238 mm x 1515 mm
Overall Thickness	14 mm (includes 2 mm pad)
Wear Surface	AC4
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Installation	Angle/Angle
Warranty	80 Hour Topical, Lifetime Residential, 15 Yr Light Commercial, 15 Yr Multi-Family
Packaging	23.29 sf/carton - 44 carton/pallet - 1024.8 sf/pallet

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Max room size up to 66' x 66' with 1/2" expansion space
- Transition molding required at rooms which join irregularly or are heated unevenly
- Subfloors dry and flat (3/16" in 10')
- Installation on or below grade concrete requires 6 mil moisture barrier

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE

