

# ALTA VISTA



5/8" THICK, ENGINEERED EUROPEAN WHITE OAK



**Apollo** | HFAVO587AP



**Fermont** | HFAVO587FM



**Santa Rosa** | HFAVO587SR



**Veranda** | HFAVO587VD

## SPECIFICATIONS

Construction	Engineered European White Oak, 3.0 mm Sawn-Cut Veneer over Multiply Core
Dimensions	7.5" Wide x Random Lengths up to 75"
Overall Thickness	5/8"
Finish Coat	High Performance UV Cured Urethane
Texture	Thermal Enhanced, Brushed
Edge Profile	4-Sided Bevel
Packaging	23.5 sf/carton - 50 carton/pallet - 1175 sf/pallet
Installation	Glue/Float/Staple (Glue Assist)
Warranty	Limited Lifetime Structural, 30 Year Residential

## INSTALLATION FAST FACTS

- Acclimate product to normal room conditions
- Moisture Content: Is recommended 7% to 9% (Not to exceed 11%)
- Relative Humidity: 40% - 55%
- Expansion Space: 7/16" gap
- Recommended Room Temp: 60°F-85°F after install
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing



SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE  
TRIMS, TRANSITIONS & QNOSE

tasflooring.com



Additional Specifications, Full Installation Instructions & Warranty Information Available Online

tasflooring.com | a division of T&A supply company, inc.